

ViziPrint®

Illuminate

ViziPrint® Illuminate is a high quality, translucent matte PET film with a halide coating for enhanced illuminated backlit displays that uses a mechanical bond to adhere graphics to glass and other smooth, flat surfaces. Thanks to its hybrid adhesive technology, no adhesive residue is left behind during graphic removal. The film is very durable and does not require overlamination for graphics. Additionally, its bright white base color and ability to diffuse light creates brighter, more vivid window images that have a wider color gamut. ViziPrint® Illuminate is reverse printable, allowing for indoor and outdoor visibility of window graphics. It is ideal for window advertisements viewed during the day in direct sunlight or illuminated at night by store lighting. It can also be used for privacy and decorative glass applications as well as backlit displays.

- IDEAL FOR INTERIOR & SHORT TERM OUTDOOR PROMOTIONS
- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED WITHOUT LEAVING ADHESIVE RESIDUE

Product Code: VPIL

100 Translucent
micron Matte
PET



Matte



Latex
UV



Hybrid
Adhesive
Technology



Widths up to 1524mm



INTERIOR



EXTERIOR*

DISPLAYS VIVID GRAPHICS DAY & NIGHT



APPLICATIONS

Smooth Flat Surfaces
Retail & Backlit Applications
Window Graphics
Decals & Stickers

Certified for
HP Latex Inks

DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

ViziPrint®

Illuminate

ViziPrint® Illuminate is a 100µ (4 mil) high quality, translucent matte PET film with a halide coating that uses a mechanical bond to adhere graphics to glass and other smooth, flat surfaces. With its hybrid adhesive technology, no adhesive residue is left behind during graphic removal. The film is very durable and does not require overlamination for graphics. ViziPrint® Illuminate is reverse printable, allowing for indoor and outdoor visibility of window graphics. Its bright white base color and ability to diffuse light creates brighter, more vivid window images that have a wider color gamut.

- IDEAL FOR INTERIOR & SHORT TERM OUTDOOR PROMOTIONS
- DIFFUSES LIGHT CREATING BRIGHTER VIVID IMAGES
- REVERSE PRINTABLE FOR INSIDE MOUNTING OF WINDOW ADVERTISEMENTS

INSTALLATION RECOMMENDATION

Wet or dry installation will work for ViziPrint® Illuminate. Please see ViziPrint® Illuminate installation instructions for further details. The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2019 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Translucent Matte PET
Adhesive	Hybrid Adhesive Technology
Release Liner	Siliconized 1 Side PET

PRODUCT CHARACTERISTIC

Film Thickness	4 mil (100µ)
*Outdoor Durability	2 Years (ink dependent; see warranty for more details)
Application Temperature	>23°F (-5°C)
Service Temperature Range	-4°F to 248°F (-20°C to 120°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PRINTING RECOMMENDATIONS

- Printing temperature should be 59-86°F (15-30°C) with 30-60% humidity. Set printer to highest print setting for optimal print quality. If mounting on glass or backlit substrates, evaluate color density of the print on a window or in transmitted light.

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com