

ReTac[®]

Smooth 150

Our 6 mil (150μ), white polymeric printable PVC film with ReTac[®] ultra removable adhesive technology is designed for graphics that need to be easily installed, removed and re-positioned.

Dimensionally stable, ReTac[®] Smooth 150 can be applied and re-positioned multiple times without stretching or tearing. And, with ReTac[®] on the back, you never have to worry about adhesive setting up, being left behind, or damaging the surface it is adhered to when graphics are removed.

ReTac[®] Smooth 150 has a Class 0 Fire Rating for surface spread of flame.

- IDEAL FOR INTERIOR WALL GRAPHIC APPLICATIONS
- PERFECT FOR APPLICATION IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS
- CAN BE REMOVED WITHOUT LEAVING ADHESIVE RESIDUE

6 mil White Phthalate-Free Polymeric PVC



Matte



(Eco) Solvent
Latex
UV



ReTac[®] ultra removable
and re-positionable
adhesive



Widths up to 61 in



5 YEARS DURABILITY
INTERIOR AND EXTERIOR
(2 YEAR REMOVABILITY EXTERIOR)

EASY APPLICATION AND REMOVAL



APPLICATIONS

Smooth Flat Surfaces

Point Of Sale Graphics

Interior Décor

Decals & Stickers

Certified for
HP Latex Inks



DRYTAC[®]
ADHESIVE SCIENCE

www.drytac.com

ReTac®

Smooth 150

ReTac® Smooth 150 is a 6 mil (150µ) printable white, phthalate-free polymeric PVC film, coated on one side with ReTac® ultra removable adhesive. The adhesive is protected by a single-sided, siliconized PE coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy application and removal of vibrant graphics to a wide range of substrates. ReTac® Smooth 150 can be easily applied, re-positioned and removed without surface damage or loss of adhesion.

- RETAC® IS A PHTHALATE-FREE FILM.
- IDEAL FOR REMOVABLE WALL DECALS, APPLIQUES AND WALL MURALS.
- SUITABLE FOR USE ON MOST INDOOR SURFACES, PAINTED WALLS, MELAMINE, GLASS, AND LOW SURFACE ENERGY SUBSTRATES.
- RETAC® SMOOTH 150 HAS A CLASS 0 FIRE RATING ACCORDING TO UK STANDARDS FOR SURFACE SPREAD OF FLAME, MAKING IT PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS, SUCH AS AIRPORTS, HOTELS AND HOSPITALS.

Please Note: Plasticizer migration from some PVC substrates could cause adhesive residue being left behind upon removal, for more information please contact your local representative.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2021 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

03082021

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

| | |
|----------------------|--|
| Film | Matte White Polymeric PVC |
| Adhesive | ReTac® ultra removable and re-positionable adhesive technology |
| Release Liner | 88# (143gsm) 1 side siliconized PE coated Kraft paper |

PRODUCT CHARACTERISTICS

| | |
|----------------------------------|---|
| Film Thickness | 6 mil (150µ) 6.9 mil (172µ) |
| Adhesive Layer | 0.9 mil (22µ) (172µ) |
| Outdoor Durability | 5 years; 2 years removability |
| Application Temperature | >41°F (5°C) |
| Service Temperature Range | 20°F to 120°F (-6.7°C to 48.9°C) |
| Flame Ratings | Class 0 (BS 476 - Part 6 & 7) Class C-s1, d0 (EN 13501-1) PASS (CAN/ULC-S102) |
| Shelf Life | 2 years |
| Storage Conditions | 59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity |

OVERLAMINATE RECOMMENDATIONS

When using ReTac® Smooth 150, an overlaminate can be used for maximum life expectancy. Products recommended for use with ReTac® Smooth 150 are Drytac's Interlam™ Pro overlaminates.

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com