

Polar®

Burst

Polar® Burst is a satin reflective print media that will vividly catch the eye of any viewer walking by and promote your product in a new and innovative way! Polar® Burst has outstanding reflective qualities that create stunning graphics which retain their vibrancy, no matter what time of day or night, as well as in wet-weather conditions. Approved for both indoor and outdoor use, it is ideal for signage and general advertising applications, as well as POP displays, posters, and other exhibition graphics.

- IDEAL FOR PROMOTIONS
- SUITABLE FOR INDOOR & OUTDOOR USE
- CAN BE EASILY REMOVED

3.7
mil

Ultra
Reflective
PVC

■
Satin



Latex
UV



Clear Removable
Acrylic
(Pressure Sensitive)



Widths up to 50 in



EXTERIOR & INTERIOR



EYE CATCHING REFLECTIVE GRAPHICS

New

APPLICATIONS

- WINDOW GRAPHICS
- DECALS & STICKERS
- POP DISPLAYS
- POS PROMOTIONS



DRYTAC®

ADHESIVE SCIENCE

www.drytac.com

Polar[®]

Burst

Polar[®] Burst is a 95 μ (3.7 mil) printable, ultra-reflective satin, self-adhesive PVC film with a high quality, removable clear acrylic adhesive protected by a siliconised PET release liner. Polar[®] Burst has great adhesion to smooth, flat surfaces. Its ultra-reflective qualities create eye-catching graphics, day and night.

- IDEAL FOR PROMOTIONS
- SUITABLE FOR INDOOR & OUTDOOR USE
- CAN BE EASILY REMOVED

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application. Use gloves to avoid fingerprints.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Satin Reflective PVC
Adhesive	Clear Removable Acrylic (Pressure Sensitive)
Release Liner	Siliconised 1 Side PET

PRODUCT CHARACTERISTIC

Film Thickness	3.7 mil (95 μ)	4.7 mil (120 μ)
Adhesive Layer	1mil (25 μ)	
Film/Adhesive Ratio	3:7.1	
UV Protection Factor	Not Applicable	
Outdoor Durability	3 years	
Application Temperature	>41°F (5°C)	
Service Temperature Range	-4°F to 248°F (-20°C to 120°C)	
Shelf Life	2 years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

DRYTAC[®]

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com