

# ViziPrint®

## Deco +

This optically clear printable window film utilizes a special ink-receptive top coat for greater adhesion of inks. ViziPrint® Deco + is ideal for architectural applications where decorative glass details are needed to create dynamic spaces, including conference rooms or private meeting areas. It can also be used to create graphics and window decals for retail storefronts and POP or backlit displays.

- IDEAL FOR HIGH QUALITY GRAPHICS FOR HIGH END RETAIL STOREFRONTS
- SUITABLE FOR CONFERENCE ROOMS AND ARCHITECTURAL APPLICATIONS.

**2** mil  
Clear  
Transparent  
PET



Gloss



UV  
Latex



Clear  
Permanent  
Acrylic (Pressure Sensitive)



Widths up to 60 in



INTERIOR



EXTERIOR

## CREATE ARCHITECTURAL APPLICATIONS



# 200m<sup>2</sup> EXHIBITIONS

## APPLICATIONS

Smooth Flat Surfaces  
Retail Backlit Displays  
Window Graphics  
Decals & Stickers

Certified for  
HP Latex Inks

This media may not be certified for all HP Latex ink and printing systems. Please check the HP media locator website at [hp.com/go/mediasolutionslocator](http://hp.com/go/mediasolutionslocator)



# DRYTAC®

ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

ViziPrint® Deco + is a 50µ (2 mil) optically clear gloss PET film, coated with a permanent clear acrylic adhesive and protected by an opaque siliconised PET release liner that has a super smooth profile to enhance the clarity when applied to glass. It has a special top coat to enhance the adhesion of inks. The film's high quality adhesive adheres to most substrates.

- IDEAL FOR HIGH QUALITY GRAPHICS FOR HIGH END RETAIL STOREFRONTS
- SUITABLE FOR CONFERENCE ROOMS AND ARCHITECTURAL APPLICATIONS.

### INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application. Use gloves to avoid fingerprints. Wet installation is recommended.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2021 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

|                      |   |
|----------------------|---|
| <b>Film</b>          | Scratch-Resistant Gloss Transparent PET with Ink-Receptive Top Coat |
| <b>Adhesive</b>      | Clear Permanent Acrylic (Pressure Sensitive)                        |
| <b>Release Liner</b> | Siliconised 1 Side PET  |

### PRODUCT CHARACTERISTIC

|                                  |  |
|----------------------------------|--|
| <b>Film Thickness</b>            | 2 mil (50µ)   2.8 mil (70µ)                                |
| <b>Adhesive Layer</b>            | 0.8mil (20µ)   (70µ)                                       |
| <b>Film/Adhesive Ratio</b>       | 2:0.8  |
| <b>Outdoor Durability</b>        | 3 Years  |
| <b>Fire Rating</b>               | Class B1 (DIN 4102-1)                                      |
| <b>Application Temperature</b>   | >41°F (5°C)  |
| <b>Service Temperature Range</b> | -4°F to 266°F (-20°C to 130°C)                             |
| <b>Shelf Life</b>                | 2 years  |
| <b>Storage Conditions</b>        | 59°F to 72°F (15°C to 22°C);<br>50 - 55% Relative Humidity |

**DRYTAC®**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013