

# FloorTac<sup>®</sup> Plus

with Interlam<sup>™</sup> Pro Emerytex<sup>®</sup>

FloorTac<sup>™</sup> Plus with Interlam<sup>™</sup> Pro Emerytex<sup>®</sup> is designed for attention-grabbing floor graphics that instantly take floors from drab to fab. Its removable, non-damaging adhesive makes this paired solution ideal for short-term indoor advertising where graphics are applied to the floor. When combined with Drytac's Interlam<sup>™</sup> Pro Emerytex<sup>®</sup> laminating films, FloorTac<sup>™</sup> Plus provides a certified slip-resistant finish for the ultimate floor graphic solution.

CAN BE APPLIED TO:

- SHORT PILE CARPETS
- CERAMIC TILES
- SEALED WOOD
- CONCRETE
- WAXED VINYL
- MARBLE, OR TERRAZZO

Product Code: PTU

**190**

micron  
(Total Solution)

Interlam Pro Emerytex  
Matte Pebble PVC Film

FloorTac Plus  
Matte White PVC Film



#### FloorTac Plus

(Eco) Solvent  
Latex  
UV



Interlam Pro Emerytex  
Pressure Sensitive Acrylic  
Adhesive

FloorTac Plus  
Removable Gray Acrylic  
Adhesive



Widths up to 1524mm



UP TO  
**9**  
MONTHS DURABILITY  
INTERIOR\*

ENGINEERED WITH NO-LIFT TECHNOLOGY



## APPLICATIONS

- SCHOOLS
- HOSPITALS
- RETAIL ADVERTISING
- SUPERMARKETS
- RESTAURANTS



**DRYTAC<sup>®</sup>**  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# FloorTac<sup>®</sup> Plus

with Interlam<sup>™</sup> Pro Emerytex<sup>®</sup>

FloorTac<sup>™</sup> Plus is an 90µ (3.5 mil printable matte white monomeric PVC film with a removable, pressure sensitive grey acrylic adhesive protected by a 120 gsm siliconized 1 side white coated paper liner.

Interlam<sup>™</sup> Pro Emerytex<sup>®</sup> is a 4 mil (100µ) monomeric soft calendared PVC laminating film with a matte pebble textured finish, coated on one side with a pressure sensitive acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconized on the release side.

- IDEAL FOR SHORT-TERM INDOOR FLOOR GRAPHICS
- SUITABLE FOR MID TO HEAVY FOOT TRAFFIC AREAS
- FOR BEST RESULTS, LEAVE A 0.25" (6MM) NON-PRINTED BORDER AROUND THE EDGE OF THE IMAGE.

\* Up to 9 months indoor durability dependent upon floor-traffic and correct installation.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

## FloorTac<sup>™</sup> PRODUCT STRUCTURE

<b>Film</b>	Matte White Monomeric PVC
<b>Adhesive</b>	Removable Gray Acrylic (Pressure Sensitive)
<b>Release Liner</b>	120 gsm Siliconized 1 Side White Coated Paper

## FloorTac<sup>™</sup> PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	3.5 mil (90µ)	4.3 mil (110µ)
<b>Adhesive Layer</b>	0.8 mil (20µ)	
<b>Application Temperature</b>	>-4°F (-20°C)	
<b>Service Temperature Range</b>	-22°F to 302°F (-30°C to 150°C)	

## Interlam<sup>™</sup> Pro Emerytex<sup>®</sup> PRODUCT STRUCTURE

<b>Film</b>	Matte Pebble Textured Monomeric PVC
<b>Adhesive</b>	Acrylic (Pressure Sensitive)
<b>Release Liner</b>	2 Side PE Coated, 1 Side Siliconised Kraft

## Interlam<sup>™</sup> Pro Emerytex<sup>®</sup> PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	4 mil (100µ)	5 mil (125µ)
<b>Adhesive Layer</b>	1 mil (25µ)	
<b>Fire Ratings</b>	Class 0 (BS 476 Part 6 and 7) Class 1 or A (ASTM E-84)	
<b>FDA Certification</b>	PASS (FDA 21 CFR 177.1975)	
<b>Slip Certifications</b>	Low Slip Potential (EN 13036-4) R 11 (DIN 51130:2010) Dry: 62; Wet: 35 (HB198:2014 (AS/NZS 4586)) Acceptable (ANSI B101.3)	
<b>Application Temperature</b>	>41°F (20°C)	
<b>Service Temperature Range</b>	-4°F to 203°F (-20°C to 95°C)	

<b>Shelf Life</b>	2 years
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

**DRYTAC<sup>®</sup>**

**ADHESIVE SCIENCE**

[www.drytac.com](http://www.drytac.com)