

FloorTac™

Textures

FloorTac™ Textures is designed for vivid floor graphics that instantly take floors from drab to fab. Its removable, non-damaging adhesive makes FloorTac™ Textures ideal for short-term indoor advertising where graphics are applied to the floor. It is slip-rated and fire rated, making it ideal for public environments where safety is a top priority.

CAN BE APPLIED TO:

- CERAMIC TILES
- SEALED WOOD
- CONCRETE
- WAXED VINYL
- MARBLE
- TERRAZZO
- SHORT PILE CARPET***

6.0
mil

Textured White
Polymeric
PVC

Matte



(Eco) Solvent**
Latex
UV



Removable
Gray Acrylic
(Pressure Sensitive)



Widths up to 54 in



MONTHS DURABILITY
UP TO
6
INTERIOR*

ONE PART FLOOR GRAPHIC SOLUTION



APPLICATIONS

SCHOOLS

HOSPITALS

RETAIL ADVERTISING

SUPERMARKETS

RESTAURANTS

DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

FloorTac™ Textures is a 6 mil (150µ) printable, matte white phthalate-free polymeric PVC film with a removable, pressure sensitive gray acrylic adhesive protected by a poly coated Kraft release liner. The textured emboss on the film provides slip resistance.

- IDEAL FOR SHORT-TERM INDOOR FLOOR GRAPHICS
- FIRE & SLIP RATED SINGLE PART FLOOR GRAPHIC SOLUTION
- FOR BEST RESULTS, LEAVE A 0.25" (6MM) NON-PRINTED BORDER AROUND THE EDGE OF THE IMAGE.

* Up to 6 months indoor durability dependent upon floor-traffic and correct installation.

***The carpet installation surface must be short pile or tightly woven, minimal texture with a limited cushion. The carpet should be clean and dry prior to application. Due to the huge variance of carpet surfaces, materials and types along with pre and post chemical treatments, a test sample is mandatory prior to production and installation. It is important that all printer and ink manufacturer guidelines are followed. The Drytac limited warranty only covers for material defect, no returns or consequential losses will be accepted.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

PRODUCT STRUCTURE

Film	Textured Matte White Polymeric PVC
Adhesive	Removable Gray Acrylic (Pressure Sensitive)
Release Liner	90# Poly Coated Kraft

PRODUCT CHARACTERISTIC

Film Thickness	6.0 mil (150µ)	7.4 mil (185µ)
Adhesive Layer	1.4 mil (35µ)	
Fire Ratings	Class 1 or A (ASTM E-84) PASS (CAN/ULC-S102)	
Slip Certifications	<ul style="list-style-type: none"> • Moderate Slip Potential; Wet: 27 (EN 13036-4/ASTM E303) • Passed (ANSI A137.1/ A326.3) • Dry: 58 Wet: 29 (AS HB198:2014 (AS/AZS 4586)) 	
Application Temperature	>-4°F (-20°C)	
Service Temperature Range	-22°F to 302°F (-30°C to 150°C)	
Shelf Life	1 year	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

**PRINTING RECOMMENDATIONS

UV and Latex inks offer the greatest durability for floor applications. Due to the variance of solvent inks it is recommended scuff resistance is tested prior to installation.

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013