

Polar®

SurfaceTac

Polar® SurfaceTac is a high quality 95 micron matte white printable monomeric PVC film that is suitable on uneven and arched surfaces. Polar® SurfaceTac is outdoor durable for 2 years making it ideal for signage and general advertising applications, including POP displays, posters and exhibition graphics as well as medium-term indoor and outdoor graphics applications.

- THE SOFTNESS AND STRETCHABILITY OF THE FILM MAKES IT SUITABLE ON UNEVEN AND ARCHED SURFACES. IT CAN BE USED FOR 2D WRAPS FOR CAR, VAN AND BUSES
- FOR USE ON FLAT PAINTED, PLASTIC, METAL, AND ACRYLIC SURFACES

Product Code: PSU

95
micron

White
Monomeric
PVC

Matte



(Eco)Solvent
Latex
UV



Grey Removable
Acrylic
Adhesive



Widths up to 1372mm



INTERIOR & EXTERIOR

STRETCHABILITY FOR UNEVEN SURFACES



APPLICATIONS

GENERAL SIGNAGE
WINDOW GRAPHICS
EXHIBITION GRAPHICS
POS DISPLAY
2D VEHICLE DECALS

DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

Polar®

SurfaceTac

Polar® SurfaceTac is a 95µ (3.8 mil) matte white monomeric PVC film, coated with a removable opaque grey acrylic adhesive that is protected by a bleached Kraft release paper coated on one side with PE and siliconized on the release side. The film's low-tack adhesive can be re-positioned during installation and easily removed from most surfaces. Polar® SurfaceTac is not recommended for use on dirty, greasy, solvent cleaned, silicone coated, or freshly painted surfaces as these can affect the film's adhesion.

- IDEAL FOR GENERAL SIGNAGE & GRAPHIC PROMOTIONS
- SUITABLE FOR INTERIOR AND EXTERIOR USE
- CAN BE APPLIED TO MANY UNEVEN AND ARCHED SURFACES

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	White Matte Monomeric PVC
Adhesive	Grey Removable Solvent Acrylic (Pressure Sensitive)
Release Liner	140 gsm Siliconized 1 Side PE Coated Kraft

PRODUCT CHARACTERISTIC

Film Thickness	3.8 mil (95µ)	4.6 mil (115µ)
Adhesive Layer	0.8 mil (20µ)	
Film/Adhesive Ratio	3.8:0.8	
UV Protection Factor	Not Applicable	
Outdoor Durability	2 Years	
Application Temperature	>41°F (5°C)	
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)	
Shelf Life	2 years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

OVERLAMINATE RECOMMENDATIONS
When using Polar™ SurfaceTac, an overlaminate can be used for maximum life expectancy. Products recommended for use with Polar™ SurfaceTac are Drytac's Interlam™, Protac™, Weathershield® or ScuffGuard overlaminates.

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013